



**VERSA
HEAT**

HRG48 SERIES 48" GAS RANGES



HRG48-24GM-4B-N

HRG48-24CH-4B HRG48-24GM-4B HRG48-24GT-4B | HRG48-8B 48" RANGE W/ 4 OR 8 BURNERS, 24" CHARBOILER OR 24" MANUAL OR THERMO GRIDDLE AVAILABLE IN NATURAL GAS OR PROPANE


- Sturdy construction for demanding commercial cooking applications
- User-friendly operation with simple controls
- Multiple function combinations: Griddle (Manual/Thermostat control), Charbroiler, & Hot plate on top with a Static oven(s), on the bottom
- 30,000 BTU per Top burner
- 35,000 BTU per Charbroiler at 12"
- 30,000 BTU per Manual or Thermostat Griddle at 12"
- 33,000 BTU per Static oven
- Oven thermostat adjusts from 200°F to 500°F (93°C to 232°C)
- Stainless steel front and back riser and lift-off high shelf
- Oven interior side guides & bottom porcelain-coated
- Shipped standard, Natural gas or LP conversion kit included.
- Optional casters available
- Gas pressure regulator is supplied with the unit

WARRANTY:
LIMITED ONE YEAR PARTS
AND LABOUR
SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT
NOTICE.

FIND
ADDITIONAL
BENEFITS
HERE




ADDITIONAL IMAGES



MODEL DESIGNATIONS



ADDITIONAL RESOURCES



TECHNICAL

Code	Gas Type	# of Ovens	# of Oven Racks	Oven BTU	TEMP RANGE °C	TEMP RANGE °F	TOTAL UNIT BTU	Opertating Gas Pressure
HRG48-24CH-4B-N	NG	2	1	30000	93°C to 260°C	200°F to 500°F	246000	5.0" W.C
HRG48-24CH-4B-P	LP	2	1	28000	93°C to 260°C	200°F to 500°F	234000	10.0" W.C
HRG48-24GM-4B-N	NG	2	1	30000	93°C to 260°C	200°F to 500°F	246000	5.0" W.C
HRG48-24GM-4B-P	LP	2	1	28000	93°C to 260°C	200°F to 500°F	218000	10.0" W.C
HRG48-24GT-4B-N	NG	2	1	30000	93°C to 260°C	200°F to 500°F	246000	5.0" W.C
HRG48-24GT-4B-P	LP	2	1	28000	93°C to 260°C	200°F to 500°F	218000	10.0" W.C
HRG48-8B-N	NG	2	1	30000	93°C to 260°C	200°F to 500°F	306000	5.0" W.C
HRG48-8B-P	LP	2	1	28000	93°C to 260°C	200°F to 500°F	272000	10.0" W.C

Code	# of Burners	Burner BTU per 12"	Total Burner BTU	Charboiler Width	Charboiler BTU per 12"	Total Charboiler BTU	Griddle Width	Griddle BTU per 12"	Total Griddle BTU
HRG48-24CH-4B-N	4	30000	120000	24"	35000	70000	-	-	-
HRG48-24CH-4B-P	4	30000	120000	24"	35000	70000	-	-	-
HRG48-24GM-4B-N	4	30000	120000	-	-	-	24"	30000	60000
HRG48-24GM-4B-P	4	30000	120000	-	-	-	24"	30000	60000
HRG48-24GT-4B-N	4	30000	120000	-	-	-	24"	30000	60000
HRG48-24GT-4B-P	4	30000	120000	-	-	-	24"	30000	60000
HRG48-8B-N	8	30000	240000	-	-	-	-	-	-
HRG48-8B-P	8	30000	240000	-	-	-	-	-	-



		Width		Depth		Height		Weight	
Code	Dimensions	Inches	mm	Inches	mm	Inches	mm	Lbs	KG
HRG48-24CH-4B-N	Exterior	48.0	1,220.0	31.4	800.0	60.0	1,530.0	536.8	244.0
HRG48-24CH-4B-P	Shipping	51.2	1,220.0	36.6	930.0	46.5	1,190.0	660.0	300.0
	Each Oven Cavity	20.0	508.0	22.5	572.0	13.3	338.0		
HRG48-24GM-4B-N	Exterior	48.0	1,220.0	31.4	800.0	60.0	1,530.0	578.6	263.0
HRG48-24GM-4B-P	Shipping	51.2	1,300.0	36.6	930.0	46.5	1,190.0	701.8	319.0
	Each Oven Cavity	20.0	508.0	22.5	572.0	13.3	338.0		
HRG48-24GT-4B-N	Exterior	48.0	1,220.0	31.4	800.0	60.0	1,530.0	578.6	263.0
HRG48-24GT-4B-P	Shipping	51.2	1,300.0	36.6	930.0	46.5	1,190.0	701.8	319.0
	Each Oven Cavity	20.0	508.0	22.5	572.0	13.3	338.0		
HRG48-8B-N	Exterior	48.0	1,220.0	31.4	800.0	60.0	1,530.0	523.6	238.0
HRG48-8B-P	Shipping	51.2	1,300.0	36.6	930.0	43.7	1,110.0	642.4	292.0
	Each Oven Cavity	20.0	508.0	22.5	572.0	13.3	338.0		

Technical drawings of the 6-burner gas cooktop showing dimensions in mm and inches:

- Top view dimensions:
 - Width: 1220mm [48"]
 - Depth: 1524mm [60,0"]
- Front view dimensions:
 - Height: 768mm [30,2"]
 - Griddle & Charbroiler Cooking area: 524mm [20,6"]
 - Gas inlet: 772mm [30,4"]
 - Side panel height: 953mm [37,5"]
- Bottom view dimensions:
 - Width: 1220mm [48"]
 - Depth: 1524mm [60,0"]
 - Griddle & Charbroiler Cooking area: 524mm [20,6"]
 - Gas inlet: 772mm [30,4"]
 - Side panel height: 953mm [37,5"]



EFI Sales Ltd.
Vancouver Office & DC
26895 Gloucester Way
Langley, BC, V4W 3Y3

(888) 565-9920 Toll Free
(519) 822-1895 Toronto
(604) 607-8850 Vancouver

